A3 Black and White Printer







SP 8400DN

GENERAL

Technology: Laser Warm-up time: 21 seconds First output speed: 2.2 seconds

A4: 60 pages per minute Print speed:

CPU: 1.46 GHz Standard: 2 GB Memory: 320 GB (Encryption/Data Overwrite HDD (option):

Security unit)

Duty cycle: 300,000 prints per month

Duplex:

Dimensions (W x D x H): 587 x 653 x 720 mm Basic model: 57 kg Weight: 220 - 240 V, 50/60 Hz Power source:

PRINTER

RAM: Standard: 2 GB Maximum: 2 GB

Maximum: 320 GB (option) HDD:

Printer language Standard: PCL5e, RPCS, PCL6(XL), PDF, PostScript 3 (emulation),

Mediaprint (JPEG/TIFF) Option: Genuine Adobe ® PostScript®

3™, XPS, IPDS, PDF Direct from

Adobe®

1,200 x 1,200 dpi Print resolution:

Fonts: PCL (93 fonts), PS3 (Emulation)

(TrueType: 93 fonts)

Interface Standard: Ethernet 10 base-T/100

base-TX/1000 base-T Option: USB 2.0, Bi-directional IEEE 1284 Wireless I AN (IFFF 802.11a/b/g/n). USB Server for Second Network Interface

TCP/IP (IP v4. IP v6) Network protocol:

Windows® 8.1, Windows® Server Windows® environments:

2008, Windows® Server 2008R2, Windows® Server 2012, Windows® Server 2012R2, Windows® Server

2016

Mac OS environments: Macintosh OS X v10.9 or later UNIX Sun® Solaris: 2.9, 2.10 UNIX environments:

HP-UX: 11.x, 11i v2, 11i v3

SCO OpenServer: 5.0.7, 6.0 RedHat® Linux Enterprise: 4, 5, 6 IBM® AIX: 5L v5.3, 5L v6.1, 5L v7.1 SAP® R/3® (SAP® R/3 3.x® or later)

PAPER HANDLING

SAP® R/3® environments:

Recommended paper size: Standard paper tray(s): A3, A4, A5, A6,

B4. B5. B6

Bypass tray: A3, A4, A5, A6, B4, B5,

Paper input capacity: Maximum: 4,700 sheets Maximum: 4,000 sheets Paper output capacity: Paper tray(s): 60 - 300 g/m² Paper weight:

Bypass tray: 52 - 300 g/m² Duplex: 52 - 256 g/m²

SECURITY

Authentication: Windows® authentication, LDAP

authentication, Basic authentication, User code authentication, 802.1.x wired authentication

Disable/Enable ports and protocols,

SSL support, SNMPv3 support

ECOLOGY

Network security:

Maximum: 1.78 kW Power consumption:

Ready mode: 43.4 W Sleep mode: Less than 0.89 W TEC (Typical Electricity Consumption)*: 0.78 kWh

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

OPTIONS

2 x 550-sheet paper tray, 2,000-sheet large capacity tray, 1,500-sheet side large capacity tray, Bridge unit, 1,000-sheet Hybrid finisher, 3,000-sheet finisher with 50-sheet stapler, 4-bin mailbox, Cabinet, Hard Disk Drive (320 GB), Wireless LAN (IEEE 802.11a/b/g/n), USB Server for Second Network Interface, Genuine Adobe @PostScript®3 $^{\text{TM}}$, IPDS unit, XPS direct print, NFC Card Reader, Internal multi-fold unit, Attention light

CONSUMABLES

Toner capacity: Black: 51,000 prints

Declared yield value:

Declared yield value in accordance with ISO/

IEC 19752

Consumable yield measuring method ISO/IEC 19752

Print Speed

4,700

For availability of models, options and software, please consult your local supplier.



















ISO9001 certified, ISO14001 certified, ISO27001 certified. All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

The new design colour touch screen on the TRAINING PRODUCT's Smart Operation Panel offers an intuitive and easy to use customer interface.

