

IM C401F/IM C40SRF

MAIN SPECIFICATIONS

IM C401F

IM C401SRF

GENERAL

Warm-up time	24 seconds	24 seconds
First copy speed: B/W	6.2 seconds	6.7 seconds
First copy speed: full colour	7.4 seconds	7.9 seconds
Continuous output speed	BW: 43 cpm, full colour: 40 cpm	BW: 43 cpm, full colour: 40 cpm
Memory: standard	6 GB	
SSD: standard	256 GB	
SSD: optional	1 TB	
HDD: optional	320 GB	
Weight	50 kg	60 kg
Dimensions: W x D x H	498 x 561 x 590 mm	615 x 561 x 706 mm
Power source	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz

COPIER

Multiple copying	Up to 999 copies
Resolution	600 dpi
Zoom	From 25% to 400% in 1% steps

PRINTER

CPU	ApolloLake E3930 1.3 GHz
Printer language: standard	PCL5c PCL6 PostScript 3 (emulation) PDF direct (emulation)
Printer language: option	Genuine Adobe® PostScript®3™ XPS PDF Direct from Adobe®
Print resolution: maximum	1,200 x 1,200/1 bit
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T USB Host IF Type A USB Device IF Type B Bluetooth Wireless LAN (IEEE 802.11 a/b/g/n/ac)
Network interface: option	Additional NIC (2nd port)
Mobile printing capability	Apple AirPrint Mopria® Ricoh Smart Device Connector
Network protocol	TCP/IP (IP v4, IP v6)
Windows® environments	Windows® 10 Windows® 11 Windows® Server 2016 Windows® Server 2019 Windows® Server 2022 Windows® Server 2025
Mac OS environments	Macintosh OS X v11 or later
UNIX environments	UNIX Sun® Solaris HP-UX SCO OpenServer RedHat® Linux Enterprise IBM® AIX

SCANNER

Scanning speed: SPDF (A4 LEF, 200dpi, B&W full colour)	40 ipm (simplex) - 80 ipm (duplex)
Resolution: maximum	1,200 dpi
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A, Single page Encryption PDF, Multi page Encryption PDF, Single/multi OCR (optional)
Scan modes	-

FAX (IM C401F, IM C401SRF)

Circuit	PSTN, PBX	PSTN, PBX
Compatibility	ITU-T (CCITT) G3	ITU-T (CCITT) G3
Transmission speed		
Modem speed: maximum	33.6 Kbps	33.6 Kbps
Scanning speed	80 spm	80 spm

PAPER HANDLING

Recommended paper size	Standard paper tray(s) (A4, A5, B5), Bypass tray (A4, A5, A6, B5, B6)	
Paper input: standard	550 sheets	550 sheets
Paper input: bypass (standard)	100 sheets	
Paper input: maximum	2,300 sheets	2,300 sheets
Paper output: max.	200 sheets	250 sheets
Paper weight	Trays (60 - 163 g/m²), Bypass (60 - 220 g/m²), Duplex (60 - 163 g/m²)	
Paper types	Plain paper, Recycled paper, Special paper, Colour paper, Letterhead, Cardstock, Preprinted paper, Bond paper, Coated paper, Envelope, Label paper	

IM C401F/IM C40SRF

MAIN SPECIFICATIONS

IM C401F

IM C40SRF

ECOLOGY

Power consumption: max.	< 1,350 W	< 1,350 W
Power consumption: ready	40.6 W	48.5 W
TEC*	0.47 kWh/week	0.48 kWh/week

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

3x 550-sheet paper tray	Paper size: (A4, A5, B5), Paper weight: (60-163 g/m ²)
One-bin tray	Tray capacity: (100 sheets), Paper size: (A4, A5, B5), Paper weight: (60-163 g/m ²)

OTHER OPTIONS

Cabinet, High cabinet, Low cabinet, Caster table, PostScript 3, Device server unit, File format converter, OCR unit, Enhanced security HDD, Page keeper, Counter I/F unit, NFC card reader, Paperlock

CONSUMABLES

Toner (black)	17,500 prints	17,500 prints
Toner (cyan/magenta/yellow)	8,000 prints	8,000 prints

Consumable yield based on 5% coverage/A4

For availability of models, options and software, please consult your local supplier.

