

B & W printers/ multifunctional products

**M 320
M 320FB
P 310**

RICOH
imagine. change.



M 320 / M 320FB / P 310 series specifications

The M 320/ M 320FB/ P310 series offers the solution that is right for your needs, whether it's just easy-to-manage and compact printing, or multifunction productivity. Compact footprints make these solutions ideal for smaller spaces and maintenance and management are simple, with intuitive operation.

Features for printers in this series include:

- Crisp 32 pages per minute output
- P 310 is ideal for use on desktops or under counters
- M 320 provides printing, scanning and copying
- M 320FB comes with 4.3 inch touch panel and ARDF
- Best in class security — including SNMPv3-encrypted communications for device monitoring, secure email transmissions by SMTP over SSL/TLS

M 320 / M 320FB / P 310

MAIN SPECIFICATIONS

	M 320	M 320FB	P 310
GENERAL			
Warm-up time	30 seconds	30 seconds	26 seconds
First copy speed: B/W		7.1 seconds	
Continuous output speed		32 ppm	
Memory: standard	256 MB	256 MB	128 MB
Weight	18 kg	18 kg	13 kg
Dimensions: W x D x H	405 x 392 x 407 mm	405 x 392 x 420 mm	370 x 392 x 262 mm
Power source	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz	220 - 240 V, 50 - 60 Hz
Laser classification	Class 1 Laser Product (IEC60825 - 1:2014)		



COPIER

Multiple copying	-	Up to 99 copies	-
Resolution	-	1,200 x 1,200 dpi	-
Zoom	-	From 25% to 400% in 1% steps	-

PRINTER

Printer language: standard	PCL5e (MAC), PCL6 (Windows & Linux), PostScript3 (Windows)
Print resolution: maximum	1,200 x 1,200 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX, USB2.0 Type B
Network interface: option	Wireless LAN (IEEE 802.11 ab/gn/ac)
Windows® environments	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019
Mac OS environments	Macintosh OS X v10.10 or later
Other supported environments	Linux environment

SCANNER

Scanning: B/W	13 ipm	13 ipm	-
Scanning: full colour	4.5 ipm	4.5 ipm	-
Resolution: maximum	600 dpi	600 dpi	-

FAX

Compatibility	-	ITU-T (CCITT) G3	-
Transmission speed	-	3 seconds	-
Modem speed: maximum	-	33.6 Kbps	-

PAPER HANDLING

Recommended paper size	Standard paper tray(s) (A4, A5, A6, B5, B6)		
Paper input: standard		300 sheets	
Paper input: maximum		550 sheets	
Paper output: standard	50 sheets	50 sheets	125 sheets
Paper weight		52 - 162 g/m ²	

ECOLOGY

Power consumption: operation	514 W	520 W	512 W
Power consumption: sleep	0.87 W	0.87 W	0.72 W
TEC*	0.423 kWh/week	0.423 kWh/week	0.408 kWh/week

OUTPUT TRAYS AND FINISHER OPTIONS

1x 250-sheet paper tray

CONSUMABLES

Starter toner	1,000 prints
Toner (regular yield)	3,500 prints
Toner (high yield)	7,000 prints

Consumable yield measuring method ISO/IEC 19752

ISO9001 certified, ISO14001 certified, ISO27001 certified

COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.

Ricoh Europe (Netherlands) B.V.

"Nieuw Kronenburg" Prof.
W.H. Keeslaan 1
1183 DJ Amstelveen
The Netherlands



+31 (0)20 5774111



ricoh-europe.com